



Product Selection Guide

FORMERRA HEALTHCARE SOLUTIONS

Patient Monitoring



Medical Wearables

The pandemic created a very different world for a lot of us, and this is more evident than ever in healthcare. An acceleration in the adoption of technology has rapidly expanded through the Internet of Medical Things. Because of this, selecting the best FDA-approved materials for skin contact, robustness, and chemical resistance is critically important while ensuring comfort, secure fit, and device accuracy through design optimization.

If you're in need of material for rigid and flexible components of your medical devices, you're in the right place. Formerra can help you solve your application challenges by providing a specialized approach to the latest material, colorant, and additive technologies. Our skilled healthcare team is committed to helping you mitigate risk, optimize design and accelerate product commercialization.



Our Suppliers

You face a unique set of challenges when designing parts for the healthcare industry. In addition to maintaining an effective manufacturing and supply chain operation, you're challenged with designing products that must meet strict regulatory and quality assurance standards. At Formerra, we help you achieve these goals with our comprehensive portfolio of leading suppliers, on-time delivery and a host of services focused on helping you succeed.



**INFUSION SET CONNECTOR
REQUIREMENTS:**

Chemical resistance, clarity,
dimensional stability

SOLUTION:

Copolyester, PMMA, MBS,
mABS

**SKIN ADHESIVE
REQUIREMENTS:**

Comfort and releasability,
durability, moisture resistant,
ability to be repositioned

SOLUTION:

Multi-layer customizable SSA
or PSA adhesives

**RESEVOIR CAP
REQUIREMENTS:**

Water ingress protection,
tetherable, UV protection,
ergonomical

SOLUTION:

Two-shot TP/TPE, PC, PP, TPV

TUBING REQUIREMENTS:

Kink resistance,
chemical resistance,
translucent, tear strength

SOLUTION:


SBC, S-TPE, TPE,
cross-linkable elastomer

**DEVICE HOUSING
REQUIREMENTS:**

Chemical resistance,
impact resistance

SOLUTION:

PBT, PC/PET, PC/PBT, PA

**DISPLAY REQUIREMENTS:**

Scratch resistance,
chemical resistance, clarity,
resistive touch capability,
toughness

SOLUTION:

Copolyester, PC, Clear ABS,
PMMA

**INSULIN PUMP HOUSING
REQUIREMENTS:**

Impact resistance, chemical resistance,
water ingress protection, hermetically
sealable, laser weldable

SOLUTION:

PBT, PC/PBT, PC, PC/ABS, TPE, TPV, laser
weldable additives

**VIAL ACCESS WINDOW
REQUIREMENTS:**

Excellent clarity, scratch resistance
and exceptional toughness for
visualization of medicant levels

SOLUTION:

PMMA, Copolyester, PC



Rigid Components

Diagnostic & Monitoring

Applications include:

- Housings
- Covers
- Clips
- Lenses
- Buttons
- Dials
- Battery panels
- Connectors
- Fasteners

Rigid Component Solution Needs:

- Materials compliant with ISO 10993 & USP Class VI, if required
- UL approved resins to meet flammability requirements, if required
- Materials that do not cause skin irritation or sensitization
- High degree of stiffness, strength and toughness to meet durability requirements
- Excellent chemical resistance to disinfectants & household cleaners, drug solutions, hand oils, lotions, sunscreen, etc.
- Broad spectrum of color & surface appearance options

Copolyester, PBT & PC/PET Blends

Copolyester	Eastman Tritan™ (Copolyester)	Durability, reliability, and toughness; impact resistance; chemical resistance to disinfectants and hand sanitizers, drug carrier solvents and lipids found in the body, or enteral feeding solutions; color retention for opaque and excellent clarity with no color shift for clear parts; no black specks; free of BPA, BPS, antimony, and halogens; high bond strength to tubing; no annealing required
Polybutylene Terephthalate (PBT)	Celanese Crastin® (PBT)	Excellent surface appearance; good printability; low extractables and volatiles; excellent gamma sterilization performance; good chemical resistance; alternative to nylon for low moisture uptake and dimensional stability; low wear/low friction (Crastin® SC164 and SC193)
	Celanese Crastin® & Rynite® (FR-PBT)	30% glass reinforced; UL94 V-0; good-excellent mold flow and electrical properties; high strength, stiffness, dimensional stability and heat resistance (Crastin® CE15330 and Rynite® FR530)
Polycarbonate/Polyester (PC/PET)	Covestro Makroblend® (FR- & Non-FR- PC/PET)	Opaque; high strength; excellent toughness; chemical resistance; skin contact biocompatibility
	Trinseo EMERGE™ (FR- & Non-FR PC/PET)	Chemical resistance to hospital disinfectants; UL94 V-0 and HB options; ISO 10993 tested

PC & PMMA

Polycarbonate (PC)	Covestro Apec® (HH-PC)	High heat transparent, strong co-polycarbonate; suitable for autoclave sterilization; good hydrolysis resistance and biocompatible
	Covestro Makrolon® (PC)	Transparent and opaque; excellent impact resistance; sterilizable by gamma, EtO, e-beam and steam; biocompatible per ISO 10993-1 and USP Class VI ; low friction options
	Trinseo EMERGE™ & CALIBRE™ (PC)	Ignition resistant; transparent and opaque options; UL94 V-0, V-2, and HB options; glass-filled also available
PolyMethyl Methacrylate (PMMA)	Trinseo Plexiglas® Acrylics (PMMA)	Water-white clarity, transparency, BPA free and ease of processing; excellent resistance to lipids and plasticizers, withstands sterilization to disinfectants such as bleach and alcohols; select grades are formulated for gamma sterilization recovery and chemical resistance; ISO 10993 and USP Class VI tested

PA, Rigid TPU & Rigid PVC

Polyamide (Nylon, PA)	Celanese Zytel® (PA66)	Good toughness, chemical resistance and colorability; excellent stiffness and strength; acceptable EtO, gamma, e-beam and autoclave sterilization (Zytel® SC310 and Zytel® FGFE5171)
	Celanese Zytel® (PA612)	Good toughness and colorability; acceptable EtO and autoclave sterilization (limited gamma/e-beam sterilization performance); improved dimensional stability, chemical resistance, and reduced aqueous extractables versus PA66 (Zytel® SC315)

PA, Rigid TPU & Rigid PVC

Rigid Thermoplastic Polyurethane (TPU)	Covestro Texin® (TPU)	Biocompatible; excellent chemical resistance; bondable to polar substrates like PC; sterilizable by gamma, EtO, e-beam and dry heat; rigid 65 to 80 Shore D grades
Rigid Polyvinyl Chloride (PVC)	GEON® Performance Solutions Resilience™ HC (PVC)	Excellent chemical resistance; maintains physical integrity and color after frequent cleaner and/or disinfectant wipe down; inherently flame retardant to UL94 5VA; high impact toughness; USP Class VI

Rigid Components

Diagnostic & Monitoring

Applications include:

- Housings
- Covers
- Clips
- Lenses
- Buttons
- Dials
- Battery panels
- Connectors
- Fasteners

Rigid Component Solution Needs:

- Materials compliant with ISO 10993 & USP Class VI, if required
- UL approved resins to meet flammability requirements, if required
- Materials that do not cause skin irritation or sensitization
- High degree of stiffness, strength and toughness to meet durability requirements
- Excellent chemical resistance to disinfectants & household cleaners, drug solutions, hand oils, lotions, sunscreen, etc.
- Broad spectrum of color & surface appearance options

Styrenics & PC/ABS Blends

Styrenics	Trinseo MAGNUM [™] (ABS) & STYRON [™] (PS)	Opaque; custom colors; excellent impact and flow; low residuals; ISO 10993 tested
	INEOS Styrolution NAS [®] (SMMA)	Sparkling clarity; color neutrality; good rigidity; easy processing; no pre-drying needed; excellent alcohol resistance
	INEOS Styrolution Zylar [®] & Clearblend [®] (MBS)	Exceptional toughness; excellent clarity; low specific gravity; no pre-drying needed; excellent thermal stability; superior chemical resistance
	INEOS Styrolution Lustran [®] (SAN)	Rigid; heat resistant; outstanding transparency; good overall chemical resistance; superior processing; good scratch resistance
	INEOS Styrolution Styrolux [®] (SBC)	Good transparency and excellent toughness; easy and versatile processing; great for adding toughness to styrenic polymer blends
	INEOS Styrolution Terluc [®] HD (MABS)	Good clarity; good heat and overall chemical resistance; good impact strength; good solvent bonding to PVC; outstanding surface quality
Polycarbonate/ABS (PC/ABS)	INEOS Styrolution Lustran [®] & Novodur [®] HD (ABS)	Opaque appearance; outstanding chemical resistance; high impact strength; excellent balance of properties; ease of processability; bondable
	Covestro Bayblend [®] (PC/ABS)	Excellent mechanical and thermal properties; toughness, rigidity & dimensional stability; opaque; biocompatible per ISO 10993-1 and USP Class VI; flame retardant options available
	Trinseo EMERGE [™] (FR- & Non-FR PC/ABS)	Ignition resistant; opaque; high flow; easy processing; UL94 V-0 and HB options; ISO 10993 tested

POM (Acetal), PP & PE

Polyoxymethylene (Acetal, POM)	DuPont [™] Delrin [®] (POM)	Excellent low wear/low friction; excellent surface appearance; good chemical resistance; alternative to nylon for low moisture uptake and dimensional stability; acceptable for EtO and autoclave sterilization (not recommended for gamma/e-beam sterilization)
Polypropylene (PP) & Polyethylene (PE)	INVISTA [™] (PP)	Good strength and stiffness; easy processing; sterilizable grades available
	Pinnacle [™] (PP)	
	Dow [™] HEALTH+ Polymers [™] (PE)	
	Lyondellbasell [™] (PP) & (PE)	

Flexible Components

Diagnostic & Monitoring

Applications include:

- O-rings
- Gaskets
- Bumpers
- Soft touch grips/handles
- Keypads/Displays
- Diaphragms
- Seals

Flexible Component Solution Needs:

- Flexible & comfortable against the body
- Water-tight seals
- Durable buttons or user interface
- Chemically resistant materials

TPE, TPC-ET, TPU, TPV & Flexible PVC

Thermoplastic Elastomers (TPE)	Avient Versaflex™ HC Overmolding Series (TPE)	Proven healthcare solutions with hardness ranges 42–65 Shore A; autoclave, radiation and EtO sterilizable; bondable to many substrates; customizable haptics
Thermoplastic Polyester Elastomers (TPC-ET)	Celanese Hytrel® (TPC-ET)	BPA-free; excellent flex fatigue and toughness; low temperature flexibility; good chemical resistance; grades ranging from 30–82 Shore D durometer
Thermoplastic Polyurethane (TPU)	Avient NEU™ Specialty Engineered Materials (TPU)	Biocompatible; various durometer ranges; autoclave, radiation and EtO sterilizable
	Covestro Texin® (TPU)	Biocompatible; soft touch; sterilizable; good chemical and abrasion resistance and toughness; excellent bonding to polar substrates like PC; 70 to 95 Shore A grades
Thermoplastic Vulcanizate (TPV)	Avient Versalloy™ (TPV)	Proven healthcare solutions with hardness ranges 45–90 Shore A; autoclave, radiation and EtO sterilizable; natural and colorable; smooth texture; bonds to PP
	Celanese Santoprene™ (TPV)	Durable sealing performance; elastic recovery; excellent chemical resistance; compliance with medical standards
Flexible Polyvinyl Chloride (fPVC)	GEON Performance Solutions Geon™ Flexible PVC	Engineered exclusively for the healthcare market; transparent and opaque colors; radiopaque grades available; durometer ranges from 55A to 40D; gamma and EtO sterilizable

Thermoset Elastomers, Thermoset Adhesives & Thermoplastic Adhesives

Thermoset Elastomers	DuPont™ Liveo™ Liquid Silicone Rubber (LSR)	Biocompatible; non-irritating and non-sensitization; sterilizable; made without plasticizers, phthalates or latex; used in Liquid Injection Molding (LIM) process
	DuPont™ Liveo™ High Consistency Rubber (HCR)	Biocompatible; non-irritating and non-sensitization; sterilizable; made without plasticizers, phthalates or latex; used in extrusion or compression molding process
Thermoset Adhesive	DuPont™ Liveo™ Soft Skin Adhesive	Skin friendly; repositionable; solventless two-part system; non-irritation and non-sensitization; used for device attachment to the skin
Thermoplastics Adhesive	DuPont™ Liveo™ Silicone Pressure Sensitive Adhesive (PSA)	Skin friendly; one-part solvent silicone adhesive; high adhesion; used for device attachment to the skin

SBC

Styrene Butadiene Copolymer (SBC)	INEOS Styrolution Styroflex® (SBC)	Rubber-like mechanics; outstanding resilience; toughness and transparency; extremely high elasticity; excellent bonding to other polymers
-----------------------------------	------------------------------------	---

Your medical wearables and handheld devices need to be durable and properly perform every time. With the right polymers, your devices will not only look great, but they will resist cracking and bring greater comfort to both the patient and the physician.

- Ambulatory Pumps
- Mobile EKG Heart Monitors
- Smart Sensor Patches
- Mobility Analysis Wearables
- Vital Signs Monitors
- Sleep Tracking Wearables
- Blood Pressure Monitors
- Pain Management Wearables
- Wearable Defibrillators
- Glucose Sensors, Monitoring & Insulin Dispensing
- Smart Clothing



Better
•
Faster
•
Smarter

Evolve How You Work With Formerra+

Formerra+ is our newly upgraded personalized online experience, designed to save time and simplify your workday.

Registered users get access to:

- Real-time pricing
- Interactive tools for seamless order management
- Instant transparency into order tracking, history and updates
- AI-powered, personalized product recommendations
- Hassle-free customer service, and more

[Shop.Formerra.com](https://shop.formerra.com)

Take The Next Step

Visit [Formerra.com](https://formerra.com) to:

- Explore solutions by material properties, industries, and suppliers
- Register for an account to gain access to personalized information, ordering, and more!

We're Here To Help

For general inquiries or customer service
Call **1.888.502.0951**

Contact Us

Capabilities

Design Support

Market Intelligence

Material Selection

Custom Formulations

Manufacturing Optimization

Technical Support

Supply Chain Optimization

Regulatory Compliance Support

Global Reach

Copyright © 2026, Formerra, LLC. All the information in this literature is for general information purpose only. Formerra makes no representations, guarantees, or warranties of any kind with respect to the information contained in this literature, including its accuracy, completeness, reliability, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for pricing, property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Formerra makes no warranties or guarantees respecting suitability of either Formerra's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. FORMERRA MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature or any other provided literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner. Any action you take upon the information you find in this literature is strictly at your own risk. Formerra will not be liable for any losses and/or damages in connection with the use of this literature. By using this literature, you hereby consent to this disclaimer and agree to its terms.